


MA/MAT HIGH-TRAFFIC DC BARRIER GATE OPERATOR

Reliable barrier operator for heavy-traffic applications.



MAT

RELIABLE

HEAVY-DUTY DC MOTOR PERFORMS IN THE MOST DEMANDING APPLICATIONS.

BATTERY BACKUP SAFEGUARDS YOUR PROPERTY WHEN THE POWER IS DOWN.

SMOOTH START/STOP OPERATION EXTENDS LIFE OF OPERATOR.

MAGNETIC LIMIT SENSORS ARE DESIGNED FOR HIGH-CYCLE APPLICATIONS.

SURGE SUPPRESSION PROVIDES INDUSTRIAL SURGE AND LIGHTNING PROTECTION.

WARRANTY OF 10 YEARS FOR ALUMINUM FRAME AND 2 YEARS FOR PARTS.

SMART

SAMS (SEQUENCED ACCESS MANAGEMENT SYSTEM) PROVIDES CONTROL BETWEEN BARRIER AND SLIDE/SWING GATE OPERATOR TO MAXIMIZE TRAFFIC FLOW.

AUXILIARY PROGRAMMABLE RELAY MAKES ADDING ADDITIONAL ACCESSORIES EASY.

MULTI-VEHICLE MEMORY ALLOWS BARRIER ARM TO REMAIN OPEN UNTIL ALL PREAUTHORIZED VEHICLES PASS THROUGH.

SAFE AND SECURE

FIRE-DEPARTMENT COMPLIANCE ALLOWS GATE TO AUTO-OPEN UPON LOSS OF AC POWER OR BATTERY DEPLETION.

BREAKAWAY ARM CAN BE EASILY REINSTALLED IF ARM IS HIT.

ANTI-TAILGATE QUICKLY SECURES PROPERTY, PREVENTING UNAUTHORIZED ACCESS.

SECURITY+ 2.0® SAFEGUARDS FACILITY ACCESS WITH ROLLING CODE TECHNOLOGY, OPENING FOR REGISTERED DEVICES ONLY.

RECOMMENDED ACCESSORIES:



LED BARRIER ARM

Aluminum arm with integrated red LED light and DOT tape provides exceptional visibility 24 hours a day.

MALED12/MALED17

LOW-POWER LOOP DETECTOR

Automatic sensitivity settings for ease of vehicle detection. Power-efficient design for max. cycles on battery backup.



LD7LP

COMMERCIAL ACCESS CONTROL RECEIVER

Standalone commercial receiver with Security+ 2.0 and IP44 housing designed for outdoor environments; can program up to 1,000 remotes for your parking or commercial applications.



STAR1000

OPTIONAL ACCESSORIES:

CONNECTED ACCESS PORTAL, HIGH CAPACITY

Cloud-based access control for residents and guests.



CAPXL

CONNECTED ACCESS PORTAL, 2-DOOR CONTROLLER

Cloud-based, credentialed access control.



CAP2D

MASTERFUL ENGINEERING.

MA/MAT

HIGH-TRAFFIC DC BARRIER
GATE OPERATOR



MA

BASE DIMENSIONS:

| | |
|-----|--------------------------------|
| MA | 41.03" H x 16.37" W x 13.50" D |
| MAT | 41.95" H x 14.46" W x 13.79" D |

OPERATOR WEIGHTS (WITHOUT ARM):

| | |
|-----------------------------|----------|
| Mega Arm Pedestal (MADCBB3) | 89 lbs. |
| Mega Arm Tower (MATDCBB3) | 113 lbs. |

MECHANICS



- 24VDC/800 RPM Continuous-Duty Motor
- 1/2 HP Equivalent
- Gear Reduction 60:1 Reducer in Synthetic Oil Bath
- Chassis: Powder-Coated 1/4 in. Aluminum Alloy

LED BARRIER ARM SPECIFICATIONS



- Arm Material: Aluminum
- Operating Voltage: 12VDC
- Lamp Type: LED 2528 IP68 Silica Gel Filled
- Color: Red/White
- Power: 14.4 W/m
- UL Listed: UL 325 and UL 991—Class I, II, III and IV
- Warranty: 6-Month Limited

TEMPERATURE SPECIFICATIONS

-13°F (-25°C) to 140°F (60°C)

| | |
|---------|---|
| MALED12 | 12 ft. x 3 in. x 2-1/4 in.; 17 lbs. (10 ft. 9-3/4 in. Installed) |
| MALED17 | 17 ft. x 3 in. x 2-1/4 in.; 25 lbs. (14 ft. Installed) |

POWER



- 120V Applications
- 220V Optional
- Accessory Power 24VDC 500 mA

COMMERCIAL-GRADE DESIGN



- Cover:
 - MA—UV-Resistant Polyethylene
 - MAT—Full Aluminum Cabinet
- UL® 325 and UL 991: Class I, II, III and IV
- Recommended Capacities:
 - Max. Arm Length—9–17 ft. Aluminum or PVC Arm
 - Cycles—6,000/Day

2.5
Seconds
to Open

SPEED

2.5
Seconds
to Close

ADDITIONAL ARM OPTIONS.

ALUMINUM

- MA024-10RDOT—Red/White Stripe Articulating Arm (10-ft. Arm Length)
- MALED12—Red/White LED Arm (12-ft. Arm Length)
- 50-ALMARMDOT—Red/White Stripe (15-ft. Arm Length)
- MALED17—Red/White LED Arm* (17-ft. Arm Length)
- MA116RDOT—Red/White Stripe** (17-ft. Arm Length)

PVC

- MA034RDOT—Red/White Stripe Articulating Arm (9-ft. Arm Length)

*Requires Counterweight MALEDCW
**Requires Counterweight MA117

FEATURES.

STANDARD

BUILT-IN 110V CONVENIENCE OUTLET

- Simplifies Adding or Powering Up Accessory Devices and Saves the Expense of Having to Add an Extra Outlet

UNIVERSAL CONTROLLER WITH 8 INPUTS

- Allows for the Connection of a Full Range of Optional External Devices

OPTIONAL

SLIP CLUTCH (MA005C)

- Allows Arm to Be Manually Pushed Open without Damaging the Gearbox or Shear Pins; Arm Automatically Resets to Normal Closed Position upon Receiving Activation

RIGHT- OR LEFT-HANDED OPERATION

- Provides Flexibility to Fit your Application and Ease of Installation

850LM RADIO RECEIVER

- Universal Receiver for Commercial Applications

HEATER (MA201/UN201)

- Maintains a Suitable Temperature Inside the Operator When Reaching Below 32°F; 150 W (MA Only) or 500 W (MAT Only)



SUPPORT.



For Support Tools and Training Videos, Visit LiftMasterTraining.com

For More Information on Gate Operators, Visit LiftMaster.com/UL325Gates

To Find the Right Perimeter Access Solution for You, Visit LiftMaster.com/Solution-Generator



Sales Support: 800.282.6225
Technical Support Center: 800.528.2806
To Order: 800.323.2276